

*G41M-S01 (MSV) Micro-ATX Mainboard Mainboard Specification * These specification is subject to change without prior notice. (MSV) /06/*

While doing the installation, be careful in holding the components and follow the installation procedures. The CPU socket has a plastic cap on it to protect the contact from damage. Before you install the CPU, always cover it to protect the socket pins. Installing Memory Modules Installing Memory Modules The memory module has only one notch on the center and will only fit in the right orientation. Insert the memory module vertically into the DIMM slot. Then push it in until the golden finger on the memory module is deeply inserted in the DIMM slot. The plastic clip at each side of the DIMM slot will automatically close when the memory module is properly seated. To connect the ATX pin power supply, make sure the plug of the power supply is inserted in the proper orientation and the pins are aligned. Then push down the power supply firmly into the connector. Page 18 IDE Connector. Refer to IDE device documentation supplied by the vendors for jumper setting instructions. If the chassis is opened, the chassis intrusion mechanism will be activated. The system will record this status and show a warning message on the screen. To clear the warning, you must enter the BIOS utility and clear the record. Follow the instructions below to set the FSB. PCI Express x16 slot. PCI Express x1 slot. Page 27 MS fail to retain data. This item applies only when synchronous DRAM is installed in the system. This setting determines the time RAS takes to read from and write to a memory cell. Remember to disable Spread Spectrum if you are overclocking because even a slight jitter can introduce a temporary boost in clock speed which may just cause your overclocked processor to lock up. This manual also for:

Chapter 2 : G41M-P26 | Motherboard - The world leader in motherboard design | MSI Latinoamérica

MS ATX Pin Power Connector JPWR1 This connector allows you to connect an ATX pin power supply. To connect the ATX pin power supply, make sure the plug of the power supply is inserted in the proper orientation and the pins are aligned.

M-ATX All items are fully tested and working unless otherwise specified. Please be aware all of our photos are stock photos, if you need a particular version or firmware revision please contact us before purchasing to ensure we have it in stock. This not only ensures data is completely wiped and privacy is protected, but also ensures that the data area and the mechanics of each and every drive we ship is sound. Please check the compatibility of products before purchasing. Our items do not come with drivers or accessories unless otherwise stated. Everything is fully tested unless otherwise stated. All payments must be clear before we will despatch any goods. If payment is not made within 5 days we will open a case to cancel the transaction. If you cannot make payment immediately please contact us so we can make arrangements. Collection in person is welcome and free from our trade counter. However please contact us before arrival so we can get the goods ready for you. We aim to ship goods the same day excluding weekends if ordered before 3pm or 1pm for courier deliveries including next day. Orders placed after 3pm on Friday will be despatched on Monday. International deliveries can take a while to arrive. Please check your tracking number using the couriers website as appropriate. However if you do have any problems please feel free to contact us. We only offer signed for postal services. This is for both our protection and yours. Please note we will not put false details on customs labels or mark items as gifts so please do not ask. We offer a 3 month RTB warranty on all of our goods unless otherwise stated. Warranty excludes items listed as spares and repairs, or for parts not working. Please contact us before returning any goods to receive free technical support and register for an RMA code. Any item returned without having an RMA will be refused by reception. Any accepted returns must be returned in original packaging within two weeks of the RMA being agreed. There is a reason we use quality boxes and anti-static bags. Please ensure items are returned in these if applicable. All returns will be tested and checked for our warranty markings. Please contact us before opening a case with eBay.

Chapter 3 : Support For G41M-P23 | Motherboard - The world leader in motherboard design | MSI Global

Msi ms ver jusb1 jusb2 - MSI Computers & Internet. Posted by Anonymous on Jan 26, Want Answer 0. Manual motherboard msi (ms) ver 2.

Chapter 4 : Msi ms ver jusb1 jusb2 - Fixya

MSI designs and creates top-tier gaming gear for gamers.

Chapter 5 : Support Center for Motherboard | MSI USA

Download MSI MS REV SCH service manual & repair info for electronics experts Service manuals, schematics, eproms for electrical technicians This site helps you to save the Earth from electronic waste!

Chapter 6 : G41M-P28 (MS) ON/OFF problem, BIOS related

MS FCC-B Radio Frequency Interference Statement. this equipment has been tested and found to comply with the limits for a class.

Chapter 7 : MSI G41M-P26 USER MANUAL Pdf Download.

G41M-P28/ G41M-P26 (MS v5.x) Intel® G41 & ICH7 chipset Handbuch herunterladen MSI G41M-P28 [Betriebsanleitung PDF]: G41M-PDE CPU ≠ Supports Intel® Core 2 Quad/Core 2 Duo based processors in LGA package.

Chapter 8 : G41M-P23 | Motherboard - The world leader in motherboard design | MSI USA

MS tRaS When the dRaM timing Mode sets to [Manual], the field is adjustable. this set- ting determines the time RaS takes to read from and write to a memory cell. *tRtP* When the dRaM timing Mode sets to [Manual], the field is adjustable. time interval between a read and a precharge command.

Chapter 9 : MSI BIOS for MSI Motherboards MS

This page contains the list of device drivers for MSI MS To download the proper driver, first choose your operating system, then find your device name and click the download button.